

Power Supplies

991824

When good enough just isn't good enough

Weidmüller 

RS-SNT, Combi-foot, TS 35/32

[Email to a Friend](#)

[View Line Drawing](#)

[Sales Information](#)

[Back to StepSearch](#)

[Catalog Home](#)



Representative Photo

Technical Information

Power Supply Type	Switchmode
Input Voltage	85...265 VAC / 95...300 VDC
Output Voltage	5 V
Output Current Rating	3 A
Housing Type	RS
Additional Data	
Rail Type	Combi Foot
Input Voltage, Minimum	85 VAC / 95 VDC
Input Voltage, Typical	115/230 VAC ±10%
Input Voltage, Maximum	265 VAC / 300 VDC
Input Voltage/Current at 120 VAC	380 mA RMS (±20%)
Input Voltage/Current at 230 VAC	200 mA RMS (±20%)
Input Voltage/Current at 125 VDC	190 mA (±20%)
Input Voltage/Current at 250 VDC	100 mA (±20%)
Frequency	50/60 Hz
In-Rush Current Protection	Thermistor
Overvoltage Protection	Varistor
Fuse	2 A, T1 (5x20 mm)
Switching Frequency	130 kHz PWM
Efficiency (at Maximum Load)	0.78
Maximum Ripple	0.1% RMS
Status Indicator	Green, power on
Maximum Capacitive Load	< 10,000 µF
Load Share	No
Load (10-100% Load)	< 1%
85 VAC to 265 VAC Line	< 0.8%
Overload Protection	Overcurrent shutdown with automatic restart plus thermal shutdown.
Dielectric Strength Input to Output	3 kV RMS

Dielectric Strength I/O to DIN-Rail	4 kV RMS
Dielectric Strength Input to Ground	1.5 kV RMS
Dielectric Strength Output to Ground	500 V RMS
Storage Temperature Range	-40°C...+85°C
Operating Temperature Range	0°C...+50°C full rated load
Wire Size	#22...14 AWG 0.5...2.5 mm ²
Clamp Screw Tightening Torque Nm (lb.in.)	0.5 (4.38)
Mechanical Dimensions (WxLxH) mm (in.)	145/109/91 (5.71"/4.29"/3.58")
Insulation Stripping Length mm (in.)	7 (.28")
Certifications	UL, CSA, CE mark, EN55022 class B, CIS PR22 class B, IEC 801-2, 3, 4, 5 level 3

Suggested Accessories

[DIN-rail](#)

[End bracket](#)

[Ferrules](#)

[Markers \(SchT\)](#)

[Marking pens](#)

[Marking tags \(DEK\)](#)

[Mounting brackets](#)

[Tools](#)

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to affirm the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Technical data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from:

Weidmüller - North America
United States 001 (800) 849-9343
Canada 001 (800) 268-4080

or

Weidmüller - Germany
Telephone operator 0049 (-5252) 960-0